

Technical Data Sheet

Page 1 of 1

Properties: AKEMI® Solid Wax is a creamy, fast drying product made of waxes and

solvents.

Application Area: AKEMI® Solid Wax is used for the treatment of window sills, corners and

edges made of fine ground or polished natural and artificial stone, e.g. marble granite, slate, travertine, terrazzo, agglomerated marble etc. It can be used indoors and outdoors. The product intensifies the natural colour and structure of the surface. Pores in the material and fine scratches are closed. Treated surfaces obtain a shiny appearance.

Instructions for Use:

1. Clean the surface thoroughly with AKEMI® Stone Cleaner. For further treatment the surface must be clean and completely dry; ideal temperature for application 15 - 25°C.

2. Apply thinly and evenly with a woolen or cotton cloth.

3. Apply several times on very absorbent, non-polished surfaces.

 Ideal condition to be polished is when surfaces appear to become dull. Remove surplus with a fine, rust-free steel-wool (fineness 00 or 000) or a clean cloth, then polish with a clean woolen or cotton cloth

5. To delay drying, dilute with AKEMI® Universal Thinner.

6. For regular cleaning use AKEMI® Mild Stone Soap.

Special Notes:

- For professional use only.

- Use afin[®] Liquid Glove to protect your hands.

 Objects in the working area which are not resistant to solvents, s.a. various synthetic materials, rubber, lacquered areas, must be protected.

 Apply Solid Wax in a thin layer only, otherwise the surface will not take a good polish.

For proper waste disposal, the container must be completely emptied.

Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.

Technical Data: Colour: transparent, black

Coverage: approx. 30 - 60 m²/liter Density: approx. 1.4 g/cm³

Storage: If stored in dry and cool condition (5-25°C/41-77°F) in its closed original

container at least 24 months from production.

Health & Safety: Read Safety Data Sheet before handling or using this product.

Important Notice: The above information is based on the latest stage of development and

application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample

piece.

TDS 02.22